



TECHNICAL DATA SHEET

fspusafallprotection.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025



FSP FS-FSP1411-W 11' CLASS A Web Retractable w/ Locking Snap Hook



Features and Benefits

FSP USA™ retractable lifelines are designed to be used as a single-person fall protection device. The FS-FSP1411-W features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall. Fall indicator sewn into webbing.

Length of Web 11 ft (3.35 m)

Weight of Unit 4 lbs (1.81 kg)

Materials

Aluminum housing
1 in (25.4 mm) Dynema webbing w/ sewn-in fall indicator
Forged steel snap hook
Steel carabiner

Hook Ratings

5,000 lbs (2267.96 kg) Tensile Strength
3,600 lbs (1632 kg) Gate Rated

Arresting Force

Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)

Maximum Arrest Distance

<24 in (609.6 mm)

Maximum Working Load

310 lbs (140.61 kg)

Webbing Tensile Strength

4,200 lbs (1905.09 kg)

Applicable Standards

Meets OSHA 1926-502 - ANSI Z359.14-2012 - ANSI A10.32-2012