



fspusafallprotection.com | (P) 704-262-7893 | (F) 704-262-9051  
 322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET



### EXTREME FS596

6' Dual-Leg Stretch Low-Profile Shock Lanyard  
 w/ Rebar Hooks



<b>Features and Benefits</b>	Fall arrest lanyard with two rebar hooks (connect to anchor points) and one snap hook (connects to harness D-ring). Elastic webbing allows for maneuverability. Rebar hook designed to fit Symons Form.
<b>Length</b>	4 ft (1.22 m) to 6 ft (1.83 m)
<b>Weight</b>	4 lbs (1.81 kg)
<b>Weight Capacity</b>	310 lbs (140.61 kg)
<b>Attachment Point(s)</b>	1 Snap hook - 2 Rebar hooks
<b>Materials</b>	1.94 in (49.28 mm) Tubular polyester webbing 1 in (25.4 mm) core stretchable webbing 0.25 in (6.35 mm) shock cord Polyester stitching grade 10 Forged steel snap hook and rebar hooks, each: 3,600 lbs Gate-rated; Min breaking strength > 5,000 lbs
<b>Applicable Standards</b>	Meets OSHA 1926-502 - ANSI Z359.13-2009 - ANSI A10.32 2012