



[fspusafallprotection.com](http://fspusafallprotection.com) | (P) 704-262-7893 | (F) 704-262-9051  
 322 Industrial Court, Concord, NC 28025



## FSP FS77430-DL-WE

6' Dual-Leg Shock-Absorbing Welding Lanyard  
 w/ Double-Locking Snap Hooks

## TECHNICAL DATA SHEET



<b>Features and Benefits</b>	Welding-rated fall arrest lanyard with three snap hooks. Hook with shock pack connects to dorsal harness D-ring. Other ends connect to anchor points. Elastic webbing. External D-ring allows for SRL attachment to convert to dual-purpose unit. Works independently allowing for proper component functionality.
<b>Length</b>	6 ft (1.83 m)
<b>Weight</b>	4 lbs (1.81 kg)
<b>Weight Capacity</b>	310 lbs (140.61 kg)
<b>Attachment Point(s)</b>	3 Snap hooks
<b>Materials</b>	1.75 in (44.45 mm) Kevlar core, Nomex cover Polyester stitching grade 10 Shock absorber Forged steel snap hooks: 3,600 lbs Gate-rated; Min breaking strength > 5,000 lbs
<b>Applicable Standards</b>	Meets OSHA 1926-502 - ANSI Z359.13-2009 - ANSI A10.32 2012